Table of Contents

I. **SAFETY SIGNS, POSTERS AND NOTICES** **2**

II. **PUBLIC LIABILITY EXPOSURES** **2**

I. SAFETY SIGNS, POSTERS AND NOTICES

Safety signs shall be posted to warn people of safety hazards. Standard signs may be available through the Loss Prevention Department or from various suppliers nationwide.

Safety posters alert people to safe practices and create a general safety awareness. Various posters are required to be posted at every jobsite and some may be available from the Safety Director. (See end of this section.)

Signs and posters shall be maintained in good condition. Faded or damaged posters and signs shall be replaced.

Safety signs shall be placed at any location where a hazard exits and as required to guide, direct and alert personnel.

Project signage should be reviewed on a regular basis and evaluate their needs and effectiveness.

II. PUBLIC LIABILITY EXPOSURES

FENCING
All fencing shall be installed to maintain safety and security of the work site. All damaged sections shall be promptly repaired. It is always a best practice to provide 100% fencing around the project's perimeter to help keep unauthorized persons off the site.

WARNING SIGNS
At the beginning of the project and during the various phases of the construction, adequate warning signs shall be posted.

BARRICADES
Barricades shall be maintained around any hazardous operation and the areas posted with warning signs. If the area is near public access, adequate lighting or warning flashers shall be provided during the hours of darkness.

PROTECTED WALKWAYS
Any type of construction which requires routing of pedestrians over sidewalks and streets must comply with local ordinances and laws. Platforms shall have guardrails and toe boards on street side and a solid high fence on building side with substantial overhead protection if needed.

Walkways shall be smooth and even, with no projections or knotholes which might cause tripping. A ramp is advisable at each end, with non-slip surface. Passageways shall be well lit with red exit lights at each end.

If equipment crosses walk, traffic shall be directed by a flagman and frequent inspection of walkway shall be made.